



Contact our sales team:

Tel: 01246 281111

Orderline email: sales@arielplastics.com

or visit www.arielplastics.com

Dry fix valley trough compatibility chart

TILE TYPE	PRODUCT
Double Lap Products	
Plain tiles (all)	DVU30DW80
Slates up to 6mm thick	DVU30DW55
Slates 7mm to 15mm thick	DVU30DW80
Slates 16mm to 22mm thick	DVU30DW105
Crest	
DS5	DVU30DW105
F12	DVU30DW105
F15	DVU30DW105
G10	DVU30DW80
H10	DVU30DW105
H14	DVU30DW105
H15	DVU30DW105
S9	DVU30DW80
Double Pantile	DVU30DW105
Double Roman	DVU30DW105
Planum	DVU30DW105
Wolds	DVU30DW105
Forticrete	
Centurion	DVU30DW105
Gemini	DVU30DW80
Minislate	DVU30DW80
Senator	DVU30DW105
V2	DVU30DW105
Koramic (Weinerberger)	
Actua	DVU30DW80
Flemish	DVU30DW105
Modula	DVU30DW105
Old Hollow	DVU30DW105
Tempest	DVU30DW105
Vauban	DVU30DW80

TILE TYPE	PRODUCT
Lagan	
Double Roll	DVU30DW105
Elite	DVU30DW80
Flat	DVU30DW80
Square Top	DVU30DW105
Marley Eternit	
Anglia Plus	DVU30DW105
Ashmore	DVU30DW80
Duo Modern	DVU30DW80
Double Roman	DVU30DW105
Edgemere	DVU30DW80
Ludlow Major	DVU30DW105
Ludlow Plus	DVU30DW105
Malvern	DVU30DW105
Maxima	DVU30DW105
Melodie	DVU30DW105
Mendip	DVU30DW105
Modern	DVU30DW80
Wessex	DVU30DW105
Quinn	
Devenish	DVU30DW80
Locherne	DVU30DW105
Rathmore	DVU30DW80
Western Slate	DVU30DW80

TILE TYPE	PRODUCT
Redland (Monier)	
49 Type	DVU30DW105
Cambrian	DVU30DW55
Cathedral	DVU30DW105
Double Roman	DVU30DW105
Duo Plain	DVU30DW80
Fenland	DVU30DW105
Grovebury	DVU30DW105
Landmark Double Pantile	DVU30DW105
Landmark Slate	DVU30DW80
Mini Stonewold	DVU30DW80
Norfolk Pantile	DVU30DW105
Old Hollow	DVU30DW105
Postel	DVU30DW105
Regent	DVU30DW105
Renown	DVU30DW105
Richmond	DVU30DW80
Saxon	DVU30DW80
Stonewold MkII	DVU30DW80
Russell	
Argyll	DVU30DW105
Cheviot	DVU30DW105
Derwent	DVU30DW105
Double Roman	DVU30DW105
Galloway	DVU30DW80
Grampian	DVU30DW80
Highland	DVU30DW80
Lothian	DVU30DW80
Moray	DVU30DW80
Pennine	DVU30DW105
Polden	DVU30DW80

TILE TYPE	PRODUCT
Sandtoft (Weinerberger)	
20/20	DVU30DW80
Arcadia	DVU30DW105
Balmoral	DVU30DW80
Bridgewater	DVU30DW105
Britlock	DVU30DW55
Calderdale	DVU30DW80
Cassius	DVU30DW80
County	DVU30DW105
Double Pantile	DVU30DW105
Double Roman	DVU30DW105
Gaelic	DVU30DW105
Greenwood	DVU30DW105
Lindum	DVU30DW105
Old English	DVU30DW105
Olympus	DVU30DW105
Neo Pantile	DVU30DW105
Rivius HDL DVLPT	DVU30DW80
Shire	DVU30DW105
Standard Pattern	DVU30DW105
TLE	DVU30DW80

Rafter Pitch	Maximum Valley Length	Minimum Lap Length
15 to 17°	10.0m	400mm
17.5 to 22.5°	12.0m	350mm
22.5 to 29°	14.5m	300mm
30 to 34°	15.0m	250mm
35 to 39°	15.5m	200mm
40 to 44°	16.5m	150mm

This table is a guide to the recommended application criteria for the Ariel Corodrain Dry Fix Valley Trough range. It assumes a standard roof intersection of 90° and roof drainage area of 100m². For applications other than this, technical advice should be sought from our sales department.

